

## **PRODUCT SPECIFICATIONS**

**RE5174 JIGGA** Thermotrak heat resistant non-metallic work boot





PRODUCT CODE: RE5174 PRODUCT NAME: JIGGA PRODUCT DESCRIPTION: Thermotrak heat resistant non-metallic work boot

| INFORMATION                                    |  |
|--|--|
| COLOUR   | Black  |
| SIZE RANGE                                     | 3 – 13 (unisex, starts from a size 3)  |
| ISO 20345 CLASSIFICATION                       | SB – NO anti-static properties   |
| SLIP RESISTANCE CLASSIFICATION SRA / SRB / SRC | SRA – tested for slip resistance in environments of ceramic surfaces with soapy solution |
| CONSTRUCTION                                   | Injection moulded construction process   |
| SABS   | SABS approved and mark bearing   |
| NRCS APPROVAL NO                               | NRCS/9002/262020/0102  |

| MATERIALS        |  |  |
|------------------|--|--|
| UPPER            | High quality full grain barton print leather                                 |  |
| SOLE             | Dual density polyurethane (PU) and rubber                                    |  |
| EYELETS          | Non-metallic high density plastic  |  |
| LINING           | Breathable and abrasion resistant taibrelle                                  |  |
| TOE CAP          | 200J composite non-metallic toe cap  |  |
| FOOTBED (INSOLE) | Moulded polyurethane (PU); taibrelle mesh upper with contoured heel and arch |  |
| INSOLE BOARD     | 3MR Ibitech non-woven insole board   |  |

| SPECIAL | FEATURES  | KEY FEATURES |
|---------|---|--------------|
| UPPER   | 200J composite non-metallic toe cap   |              |
| SOLE    | Outsole is heat resistant up to 300°C   |              |
| OTHER   | No breakdown at AC voltage raised at 5kVs per minute up to 20Kv and held for 60 seconds. Compliant with ESKOM SPEC 34-232 | NST NST      |
|         |   |              |

## **SUGGESTED ENVIRONMENTS**

Electricians, engineering, mining, chemical and petrochemical, refineries, welders/foundries and smelters.

